

Product Name: PHT50 Black

SDS No.: 037-W557291 First issue: 2022/12/05 Revised: 2025/07/23

1. Identification

Product Name : PHT50 Black Order No. : PHT50-K-60

General Use : Inkjet printing ink

Product Description : Water based pigment ink

SDS Number : 037-W557291

Manufacture

Company Name : Mimaki Engineering Co., Ltd.

Address : 2182-3 Shigeno-otsu, Tomi-shi, Nagano 389-0512 JAPAN

Telephone No. : +81-268-64-2413

Importer / Distributor Established in USA

Company Name : MIMAKI USA, INC.

Address : 4851 Thurmon Tanner Parkway, STE 100 Flowery Branch, GA

30542, U.S.A.

Telephone No. : +1-678-730-0170

Emergency Telephone : +1 866 928 0789 (within United States only, Toll free)

No. +1 215 207 0061

2. Hazards Identification

[HCS Classification]

Physical Hazards

Flammable Liquids : Not classified

Health Hazards

Not classified

Environmental Hazards

Not classified

The above list does not include category being non-classifiable or not-applicable.

[HCS Label Elements]

Symbol

None

Signal Word

None

Hazard Statements



Product Name: PHT50 Black

SDS No.: 037-W557291 First issue: 2022/12/05 Revised: 2025/07/23

None

Precautionary Statements

[Prevention]
None
[Response]
None
[Storage]
None
[Disposal]

None

3. Composition / Information on Ingredients

No	Chemical Name	Wt%	CAS No.
1	Water	65-75	7732-18-5
2	Diethylene Glycol	10-20	111-46-6
3	Glycerol	1-10	56-81-5
4	Polyurethane resin	1-10	Trade Secret
5	Carbon Black	1-10	1333-86-4

4. First Aid Measures

Inhalation : Move victim into fresh air. If breathing is difficult, give oxygen and

consult a physician immediately.

Eye Contact : Rinse thoroughly with plenty of water for at least 15 minutes and

consult a physician if feel uncomfortable.

Skin Contact : Wash with plenty of soap and water. Take off contaminated clothing

and wash before re-use. If skin irritation or rash occurs: Get medical

advice/attention.

Ingestion : Never give anything by mouth to an unconscious person. Call a

physician or Poison Control Center immediately.

Most Important Symptoms/Effects

Acute : Based on available data, the classification criteria are not met.

Delayed : Based on available data, the classification criteria are not met.

Indication of Immediate : Treat symptomatically. Symptoms may be delayed.

Medical Attention and



Product Name: PHT50 Black SDS No.: 037-W557291 First issue: 2022/12/05

Revised: 2025/07/23

Special Treatment Needed, If Needed

Fire Fighting Measures

: Flash point Not flammable Flammable Properties

Extinguishing Media : Use extinguishing media suitable for surrounding area.

Unsuitable Extinguishing : There is no restriction on the type of extinguisher which may be

Media

used.

Special Hazards Arising

: Development of hazardous combustion gases or vapor possible in the

from the Chemical

event of fire.

Special Protective

: As in any fire, wear self-contained breathing apparatus

Equipment and

(MSHA/NIOSH approved or equivalent) and full protective gear.

Precautions for

Fight fire from a safe distance, with adequate cover.

Firefighters

Prevent fire extinguishing water from contaminating surface water

or the ground water system.

Accidental Release Measures

: Use personal protective equipment, do not breathe Personal Precautions,

Protective Equipment

gas/mist/vapour/spray.

and Emergency

Ensure adequate ventilation. Remove all sources of ignition. Take

Procedures

precautionary measures against static discharges.

Evacuate personnel to safe areas. Keep people away from and upwind

of spill/leak.

Methods and Materials

: Cut off the source of the leak as much as possible.

for Containment and

Keep leaks in a ventilated place.

Cleaning Up

Absorb spilled material in dry sand or inert absorbent. In case of

large amount of spillage, contain a spill by bunding.

Remove all sources of ignition. Use spark-proof tools and

explosion-proof equipment.

Contain spillage, and then collect with an electrically protected

vacuum cleaner or by wet-brushing and place in container.

Environmental : Prevent further leakage or spillage if safe to do so.

precautions Discharge into the environment must be avoided.



Product Name: PHT50 Black SDS No.: 037-W557291

> First issue: 2022/12/05 Revised: 2025/07/23

7. Handling and Storage

Precautions for Safe : Handling is performed in a well ventilated place.

Handling Avoid contact with eyes.

Keep away from heat/sparks/open flames/ hot surfaces.

Conditions for Safe : Keep containers tightly closed.

Storage, including any Keep containers in a dry, cool and well-ventilated place.

Incompatibilities Keep away from heat/sparks/open flames/hot surfaces.

Store away from incompatible materials and foodstuff containers.

8. Exposure Controls / Personal Protection

Exposure Limit Values

No	Chemical Name	ACGIH (TLV)	OSHA (PEL)	
			15 mg/m³ TWA (mist, total particulate)	
1	Glycerol (56-81-5) Not established	Not ostablished	5 mg/m³ TWA (mist, respirable fraction)	
		(Vacated) 10 mg/m³ TWA (mist, total particulate)		
			(Vacated) 5 mg/m³ TWA (mist, respirable fraction)	
		3 mg/m3 TWA		
0	Carbon Black	(inhalable	3.5 mg/m3 TWA	
2	(1333-86-4)	particulate	(Vacated) 3.5 mg/m3 TWA	
		matter)		

Component Biological

: No relevant regulations

Limit Values

Exposure Controls

Occupational Exposure Controls

Appropriate : Ensure adequate ventilation, especially in confined areas.

workstation location.

Set up emergency exit and necessary risk-elimination area. Handle in accordance with good industrial hygiene and safety

practice.

Individual Protection Measures, such as Personal Protective Equipment

Respiratory Protection : Consult with a health and safety professional for specific respirators



SDS No.: 037-W557291 First issue: 2022/12/05

Revised: 2025/07/23

Product Name: PHT50 Black

Safety Data Sheets



appropriate for your use.

Glove : Wear appropriate chemical resistant gloves.

Recommendations



Eye /Face : Wear coverall, chemical goggles and face shield when handling.

Protection



Skin Protection : To prevent any contact, wear impervious clothing such as gloves,



apron, boots, or whole body suits made from neoprene, as appropriate.

Physical and Chemical Properties

- Physical State : Liquid Appearance

> - Color : Black

Odor : No information available

: 7-9 рН

Boiling Point / Boiling Range : No information available Melting Point / Melting Range : No information available : No information available **Decomposition Temperature**

Flash Point : Not flammable

Auto ignition temperature : No information available

Flammability (Solid, Gas) : Not flammable

: No information available **Explosive Properties** : No information available Oxidizing Properties Upper / Lower Flammability or : No information available

Explosive Limits

Vapor Pressure

: No information available Relative Density



Product Name: PHT50 Black SDS No.: 037-W557291

First issue: 2022/12/05 Revised: 2025/07/23

Solubility : No information available
Water Solubility : No information available
Partition Coefficient (n-octanol / Water) : No information available

Viscosity : 3-5mPa · s

Vapor Density : No information available
Evaporation Rate : No information available
VOC : No information available

10. Stability and Reactivity

Conditions to Avoid : Incompatible materials, heat, flame and spark.

Stability : Stable under proper operation and storage conditions.

Materials to Avoid : Alkali, sodium, calcium, and other active metal, halogen, metal oxide,

nonmetal oxide, acyl halide and metal phosphide. Oxidants, alkali

metals, alkaline earth metals and aluminum.

Hazardous Reactions /

: Contact with incompatible substances can cause decomposition or

Decomposition Products other chemical reactions.

In contact with active metals (alkali metals, Na, Ca etc.) causes a reaction and release hydrogen. In contact with oxidants causes severe

reactions, and may cause a fire or explosion.

Under normal conditions of storage and use, hazardous decomposition

products should not be produced.

11. Toxicological Information

Acute Toxicity : Glycerol (56-81-5)

Oral LD₅₀ Rat 12,600 mg/kg

Dermal LD₅₀ Rabbit >10,000 mg/kg

: Carbon Black (1333-86-4)

Oral LD₅₀ Rat >15,400 mg/kg

Dermal LD₅₀ Rabbit >3,000 mg/kg

Skin corrosion/irritation : Based on available data, the classification criteria are not met

Serious eye : Based on available data, the classification criteria are not met

damage/irritation

Respiratory : Based on available data, the classification criteria are not met

sensitization



Product Name: PHT50 Black SDS No.: 037-W557291

First issue: 2022/12/05 Revised: 2025/07/23

Safety Data Sheets

Skin sensitization : Based on available data, the classification criteria are not met

Germ Cell Mutagenicity : Based on available data, the classification criteria are not met

Carcinogenicity : Based on available data, the classification criteria are not met

Reproductive toxicity : Based on available data, the classification criteria are not met

Specific Target Organ : Based on available data, the classification criteria are not met

Toxicity - Single

Exposure

Specific Target Organ

Toxicity - Repeated

Exposure

Aspiration hazard : Based on available data, the classification criteria are not met

12. Ecological Information

Handling is noted because it might influence the environment when

: Based on available data, the classification criteria are not met

leaking and abandoning it.

Especially, note that the product doesn't flow directly to ground, the

river, and the drain ditch.

Ecotoxicity (Acute : Glycerol (56-81-5)

aquatic toxicity) LC₅₀ Fish 885 mg/L(96h)

: Carbon Black (1333-86-4)

LC₅₀ Fish >1,000 mg/L(96h)

Ecotoxicity (Chronic

: No information available.

aquatic toxicity)

Mobility : No information available for the product.

Persistence and : No information available for the product.

Degradability

Bioaccumulative : No information available for the product.

Potential

Other Adverse Effects : No information available for the product.

13. Disposal Considerations

: Comply with all USA, national and local regulations.

Do not dump this product into sewers, on the ground or into any body

of water.



Product Name: PHT50 Black SDS No.: 037-W557291

First issue: 2022/12/05 Revised: 2025/07/23

Safety Data Sheets

Waste chemicals : Recommend the use of incineration disposal.

Contaminated : Containers may still present chemical hazard when empty. Keep

packaging away from hot and ignition source of fire.

14. Transport Information

Check a thing without a leak in a container.

Perform prevention of collapse of cargo surely.

IMDG-CODE
 IATA-DGR
 Not regulated as dangerous goods for transport.
 UN-ADR
 Not regulated as dangerous goods for transport.

15. Regulatory Information

OSHA Status : This product is not considered to be hazardous under 29 CFR 1910.1200.

TSCA Status : Polyurethane resin (Trade Secret) Yes

Glycerol (56-81-5) Yes

Carbon Black (1333-86-4) Yes

Other regulatory

California Proposition 65 : WARNING



This product can expose you to chemicals including Carbon black and Ethylene glycol which are known to the State of California to cause cancer / birth defects or other

reproductive harm. For more information go to

www.P65Warnings.ca.gov.

16. Other Information

References 1) SDS of raw material

2) IPCS: The International Chemical Safety Cards (ICSC)

This information is furnished without warranty, express or implied, except that it is accurate to the best knowledge of Mimaki Engineering Corporation.

It relates only to the specific material designated herein, and does not relate to use in combination with any other material or process.



Product Name: PHT50 Black SDS No.: 037-W557291

> First issue: 2022/12/05 Revised: 2025/07/23

Mimaki Engineering Corporation assumes no legal responsibility for use or reliance upon this information.